Thompson
Meat Machinery

Mk3 Bandsaw



LEADING MANUFACTURERS OF MEAT PROCESSING MACHINERY

Thompson Mk3 Bandsaw

Construction

The Thompson Mk3 Bandsaw offers a reliable smooth cutting operation delivered by a direct drive motor system.

The Thompson Mk3 Bandsaw is constructed from high quality stainless steel and offers many features normally associated with more expensive machinery.



Outstanding Features

- Stainless steel construction.
- Direct drive operation.
- Automatic blade tensioning.
- Mehanite steel flywheels with blade relief and retaining shoulders to ensure bandsaw blade cannot be dislodged from the wheel surface.
- Stainless steel blade scrapers.
- Simple and quick disassembly of machine for cleaning.

Recommended Options

- Heavy duty emergency stop kick switch.
- Brake with approx. 2 second stopping capability.

Options

- Stainless steel flywheels.

Specifications

OVERALL HEIGHT:	2000
TABLE SIZE:	750 x 850
CUTTING HEIGHT (MAX):	440
CUTTING WIDTH:	400
FLOOR AREA:	860 x 900
FLOOR TO TABLE:	970
DRIVE:	1.5Kw 8 Pole
POWER SUPPLY STD.:	10 AMP
POWER SUPPLY WITH BRAKE:	recommended, 20 AMP outlet with curve 1 circuit breaker
STARTING CURRENT:	11.6 A
BLADE LENGTH:	3290 mm (10'91/2")
BLADE WIDTH:	16 mm
BLADE SPEED:	950 m/min (3100 ft/min)
WEIGHT:	182 kgs
SHIPPING WEIGHT:	233 kgs
SHIPPING SIZE:	1000 x 1000 x 2000h

Thompson Meat Machinery

Also Trading as E.L. Sammon & CO.

134 Magnesium Drive, Crestmead Brisbane, Qld Australia 4132

Phone +61 7 3803 6643 — fax +61 7 3803 6635

Email **sales@tmach.com.au** — Web Site **www.tmach.com.au**