

MILL TEST CERTIFICATE

NAME OF COMMODITY	Steel strapping	STANDARD	MANUFACTURER'S SPECIFICATIONS
SPECIFICATION	0.56×19mm	DATE OF PRODUCTION	2015-10
INSPECTION ITEMS	STANDARD VALUE	ACTUAL VALUE	
TOLERANCE OF THICKNESS	±0.030MM	0.56 0.57 0.57 (MM)	
TOLERANCE OF WIDTH	±0.10MM	19 19 19 (MM)	
TENSILE STRENGTH	≥700MPA	795 830 760(MPA)	
ELONGATION	≥3%	3.5% 4.3% 3.8%	
COLOUR	black	black	
WEIGHT	15±1kg	14.8 14.9 15.1 (Kg)	
PACKING	Compound paper	Compound paper	
OTHERS	Fe	99-99.99(%)	99.236%
	C	0.09-0.20(%)	0.12 %
	Si	0.15-0.30(%)	0.17 %
	Mn	0.35-0.50(%)	0.40 %
	S	0.02-0.03(%)	0.022%
	P	0.015-0.020(%)	0.016 %
	Cr	0.010-0.020(%)	0.011%
	Nr	0.010-0.020(%)	0.012%
	Cu	0.010-0.020(%)	0.013%
APPRAISE	QUALIFIED	REMARK	Steel Grade:Q235
STAMP		INSPECTOR	丰长英

OCT,2015